

Opella-XD

High-performance Ashling Debug Probe



Opella-XD is Ashling's high-performance Debug Probe for embedded development with support for multiple target architectures including RISC-V, Arm-Cortex, MIPS (P8700 & I8500) & Synopsys ARC-V & ARC powered systems.

Opella-XD works with Ashling's [RiscFree™](#) SDK for advanced embedded system debugging & on-chip tracing.

Features

- Up to 3MB/s download speeds making it suitable for large, complex, software-intensive projects.
- Supports JTAG, EJTAG, cJTAG & CoreSight™ SWD & DAP debug interfaces with fine-grained adjustment of clock frequency from 1kHz to 100MHz.
- Auto-conditioning ensures maximum possible download speed with fastest JTAG clock frequencies.
- Hot-plug support – allows connection to a running target without resetting or halting.
- Heterogeneous (e.g., Arm + RISC-V) & homogeneous debug support for multi-core SoCs sharing a single debug interface (e.g., via JTAG, cJTAG or CoreSight™ DAP & SWD).
- Supports 32-bit & 64-bit target devices.
- Powered by USB2 interface – no external power-supply required.
- Fast, trouble-free "Plug-and-play" installation & configuration.
- **Opella-XD** detects & automatically configures for the appropriate target voltage (0.9v to 3.6v).
- Low-level JTAG command-line console and APIs for device bring-up etc.
- Display/read/write of target system memory & peripheral registers.
- Support for on-chip hardware breakpoints – unlimited software breakpoints.
- Run/stop control of target application including go, halt, step over, step into & step out.
- Configurable Target-Reset & Test-Port-Reset, under full user control.
- Built-in diagnostics instantly show status of Target, Debug Probe & USB link.



Product	Order Code
Opella-XD Debug Probe (with 20-way 0.1" target interface)	OPELLA-XD
Optional 14-way 0.1" adapter for EJTAG targets	AD-EJTAG-14
Optional 10-way 0.05" adapter for MIPI/CoreSight targets	AD-CS-10
Optional 12-way 0.1" adapter for RISC-V targets	OPXD_TPA_RISC-V_ADAPTER
Optional 6-way cJTAG/JTAG 0.1" adapter	AD-ARC-6JTAG